



TECHNISCHE INFORMATION / TECHNICAL INFORMATION

Type SI/2 blau AS 1261



Tradition and innovation since 1929

Einsatzgebiete	Aufgabe- und Abnahmestationen
Eigenschaften	Öl- und Fettbeständig, Querstabil
Gewebe	BRA
Lagenzahl	2
Zugkraft bei 1% Dehnung N/mm Bandbreite	10
Beschichtung Tragseite	Silicone, 55 Shore A
Beschichtung Laufseite	Gewebe- Imprägnierung
Farbe	blau
antistatisch	ja
Lebensmitteleignung	EU FDA
Dicke mm	1,6
Gewicht g/m ²	1.800
min. Walzen-Ø mm	40
Temperaturbeständigkeit °C	-30 bis +120
Reibungskoeffizient auf Stahl Laufseite	0,2
Empfohlene Dehnung N/mm	4,0-7,0

fields of application	feeding ans sorting machines
properties	oil and fat resistant, transversely stability
fabric	BRA
number of plies	2
tractive power for 1% tension N/mm belt width	10
coating material carrying side	Silicone, 55 Shore A
coating material running side	Fabric- impregnation
colour	blue
antistatic	yes
certificate about food applicability	EU FDA
thickness mm	1,6
weight g/mm ²	1.800
min. roller-Ø mm	40
temperature stability °C	-30 to +120
friction value on steel running side	0,2
recommended stretch N/mm	4,0-7,0